


## BOTTOM MOUNT REACH-IN REFRIGERATORS

Atlas Air's Bottom Mount Reach-in Refrigerators are a great addition to your restaurant or commercial kitchen. With a stainless steel exterior, bright white interior, forced air refrigeration system and digital thermostat microprocessor, your food products are sure to maintain consistent temperatures of 33°F to 41°F even in the busiest kitchens.



<b>Brand</b>	Atlas Air Commercial Refrigeration		 <b>ATLAS AIR®</b>
<b>Model Numbers</b>		<b>A1</b>	<b>A2</b>
<b>Dimensions &amp; Construction</b>	Interior Capacity (cu/ft)	22	47
	Exterior Size WxDxH (inches)	27 x 32 x 83 1/2	54 1/10 x 32 x 83 1/2
	Interior Size WxDxH (inches)	23 x 24 3/8 x 60 1/2	50 1/4 x 24 3/8 x 60 1/2
	Exterior Construction	High polished stainless steel	
	Interior Construction	Bright white powder coated aluminum	
	Air Plenum	Full length for even air distribution	
	Shelves	3 white epoxy coated wire	3 white epoxy coated wire
	Handle	ABS Plastic, recessed	
	Solid Door	1 Stainless Steel Door	2 Stainless Steel Doors
	Door Gasket	Tongue and groove, easy to clean & replace	
	Hinges	Stainless steel	
	Pilasters and Shelf Clips	Stainless steel	
	Floor	Rounded, coved corners	
Casters	(2) Locking, (2) non-locking	(2) Locking, (2) non-locking	

<b>Refrigeration System</b>	Temperature Range	33°F to 41°F	33°F to 41°F
	Refrigeration System	Forced Air	Forced Air
	Refrigerant	R290	R291
	Expansion Device	Capillary Tube	
	Defrost method	Automatic	
	Compressor Type	Hermetic compressor	
	Condenser Type	Air cooled, electrostatic coated copper tube	
	Evaporator Type	Air cooled, electrostatic coated copper tube	
	Humidity control	Hot gas condensation evaporation	
<b>Electrical System</b>	Power	115/60/1	115/60/1
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P
	Horse Power	1/6	1/5
	Kilowatts per 24 Hours	1.15	1.87
	Amperage	2.7	3.7
<b>Packaging &amp; Shipping Info</b>	Shipping Dimensions		
	Shipping Weight		
	Palletized	Yes, wood, front/back loading	
	Material	Wood, card board, Styrofoam, plastic wrap	
	UPC GTIN		
<b>Digital Temperature Controller</b>	Digital Temperature Microprocessor	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.	
	Keypad	Adjustable, tactile keypad	
	Screen	2" blue LCD	2" blue LCD
	Water resistant	Yes	Yes
<b>Warranty</b>	Compressor	5 Years	5 Years
	Parts	2 Years	2 Years
	Labor	2 Year	2 Year
<b>Certifications</b>	<b>ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)</b>		
<b>Application</b>	For Commercial Kitchens (not for residential use)		
<b>Company Motto</b>	Best Build, Period.		