


# GLASS DOOR MERCHANDISER REFRIGERATORS



Atlas Air's Bottom Mount, Glass Door Merchandiser Refrigerators will elegantly and brightly display your food products for sale. With a black powder coated steel exterior, bright white interior, forced air refrigeration system and digital thermostat microprocessor, your food products are sure to maintain consistent temperatures of 33°F to 41°F while offering a pleasant, high quality merchandising experience for your customer.



<b>Brand</b>	Atlas Air Commercial Refrigeration			 <b>ATLAS AIR®</b>
<b>Model Numbers</b>		AM19	AM45	AM70
<b>Dimensions &amp; Construction</b>	Interior Capacity (cu/ft)	19,2	44,7	70
	Exterior Size WxDxH (inches)	27 x 33 1/2 x 83	54 x 33 1/2 x 83	80 3/4 x 33 1/2 x 83
	Interior Size WxDxH (inches)	22 3/8 x 27 3/4 x 61 1/2	49 3/8 x 27 3/4 x 61 1/2	76 1/8 x 27 3/4 x 61 1/2
	Exterior Construction	Black powder coated steel		
	Interior Construction	Bright white powder coated aluminum		
	Air Plenum	Full length for even air distribution		
	Shelves	3 white epoxy coated wire	3 white epoxy coated wire	3 white epoxy coated wire
	Handle	ABS Plastic, recessed		
Glass Door	1 Dual Pane, ABS plastic frame, swinging	2 Dual Pane, ABS plastic frame, swinging	3 Dual Pane, ABS plastic frame, swinging	

	Door Gasket	Tongue and groove, easy to clean & replace	Tongue and groove, easy to clean & replace	Tongue and groove, easy to clean & replace
	Hinges	Stainless steel		
	Pilasters and Shelf Clips	Stainless steel		
	Floor	Rounded, coved corners		
	Casters	(2) Locking, (2) non-locking	(2) Locking, (2) non-locking	(2) Locking, (2) non-locking
<b>Refrigeration System</b>	Temperature Range	33°F to 41°F	33°F to 41°F	33°F to 41°F
	Refrigeration System	Forced Air	Forced Air	Forced Air
	Refrigerant	R290	R291	R292
	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube
	Defrost method	Automatic	Automatic	Automatic
	Compressor Type	Hermetic compressor		
	Condenser Type	Air cooled, electrostatic coated copper tube		
	Evaporator Type	Air cooled, electrostatic coated copper tube		
	Humidity control	Hot gas condensation evaporation		
<b>Electrical System</b>	Power	115/60/1	115/60/1	115/60/2
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P
	Horse Power	1/6	1/5	3/8
	Kilowatts per 24 Hours	1.7	3.4	6.3
	Amperage	2.8	3.8	5.8
<b>Packaging &amp; Shipping Info</b>	Shipping Dimensions			
	Shipping Weight			
	Palletized	Yes, wood, front/back loading	Yes, wood, front/back loading	
	Material	Wood, card board, styrofoam, plastic wrap	Wood, card board, styrofoam, plastic wrap	
	UPC GTIN			
<b>Digital Temperature Controller</b>	Digital Temperature Microprocessor	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.	

	Key Pad	Adjustable, tactile key pad	Adjustable, tactile key pad	
	Screen	2" blue LCD	2" blue LCD	
	Water resistant	Yes	Yes	
<b>Warranty</b>	Compressor	5 Years	5 Years	
	Parts	2 Years	2 Years	
	Labor	2 Year	2 Year	
<b>Certifications</b>	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)	
<b>Application</b>	For Commercial Kitchens (not for residential use)			
<b>Company Motto</b>	Best Build, Period.			

