




UNDER COUNTER REFRIGERATORS

Atlas Air's Under Counter Refrigerators are a great, space saving addition to your restaurant or commercial kitchen. With a stainless steel exterior, bright white interior, forced air refrigeration system and digital thermostat microprocessor, your food products are sure to maintain consistent temperatures of 33°F to 41°F even in the busiest kitchens.



Brand	Atlas Air Commercial Refrigeration				 ATLAS AIR®	
Model Numbers		AU27	AU48	AU60	AU72	
Dimensions & Construction	Interior Capacity (cu/ft)	6,7	11,1	14,1	16,6	
	Exterior Size WxDxH (inches)	29x30 3/8x38 3/8	48x30 3/8x38 3/8	61x30 3/8x38 3/8	72x30 3/8x38 3/8	
	Interior Size WxDxH (inches)	31x35 1/4x40	43x23 3/8x26 5/8	56x23 3/8x26 5/8	67x23 3/8x26 5/8	
	Exterior Construction	High polished stainless steel				
	Interior Construction	Bright white powder coated aluminum				
	Shelves	1 white epoxy coated wire	2 white epoxy coated wire	2 white epoxy coated wire	3 white epoxy coated wire	
	Handle	ABS Plastic, recessed				
	Solid Door	1 Stainless Steel Door	2 Stainless Steel Doors	2 Stainless Steel Doors	2 Stainless Steel Doors	
	Door Gasket	Tongue and groove, easy to clean & replace				
	Hinges	Stainless steel	Stainless steel	Stainless steel	Stainless steel	
Pilasters and Shelf Clips	Stainless steel	Stainless steel	Stainless steel	Stainless steel		

	Floor	Rounded, coved corners			
	Casters	(2) Locking, (2) non-locking			
	Temperature Range	33°F to 41°F	33°F to 41°F	33°F to 41°F	33°F to 41°F
	Refrigeration System	Forced Air	Forced Air	Forced Air	Forced Air
	Refrigerant	R290	R291	R292	R293
	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube	Capillary Tube
	Defrost method	Automatic	Automatic	Automatic	Automatic
	Compressor Type	Hermetic compressor			
	Condenser Type	Air cooled, electrostatic coated copper tube			
	Evaporator Type	Air cooled, electrostatic coated copper tube			
	Humidity control	Hot gas condensation evaporation			
	Power	115/60/1	115/60/1	115/60/1	115/60/1
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P
	Horse Power	1/6	1/6	1/6	1/4
	Kilowatts per 24 Hours				
	Amperage	2.8	2.8	2.8	4.2
	Shipping Dimensions				
	Shipping Weight				
	Palletized	Yes, wood, front/back loading			
	Material	Wood, card board, styrofoam, plastic wrap			
	UPC GTIN				
	Digital Temperature Microprocessor	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.			
	Key Pad	Adjustable, tactile key pad			
	Screen	2" blue LCD	2" blue LCD	2" blue LCD	2" blue LCD
	Water resistant	Yes	Yes	Yes	Yes
Warranty	Compressor	5 Years	5 Years	5 Years	5 Years
	Parts	2 Years	2 Years	2 Years	2 Years
	Labor	2 Year	2 Year	2 Year	2 Year
	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)				
Application	For Commercial Kitchens (not for residential use)				
Company Motto	Best Build, Period.				

