




UNDER COUNTER FREEZERS

Atlas Air's Under Counter Freezers are a great, space saving addition to your restaurant or commercial kitchen. With a stainless steel exterior, bright white interior, forced air refrigeration system and digital thermostat microprocessor, your food products are sure to maintain consistent temperatures of 33°F to 41°F even in the busiest kitchens.



Brand	Atlas Air Commercial Refrigeration			 ATLAS AIR®
Model Numbers		AU27F	AU48F	AU60F
Dimensions & Construction	Interior Capacity (cu/ft)	6,7	11,1	14,1
	Exterior Size WxDxH (inches)	29x30 3/8x38 3/8	48x30 3/8x38 3/8	61x30 3/8x38 3/8
	Interior Size WxDxH (inches)	31x35 1/4x40	43x23 3/8x26 5/8	56x23 3/8x26 5/8
	Exterior Construction	High polished stainless steel		
	Interior Construction	Bright white powder coated aluminum		
	Shelves	1 white epoxy coated wire	2 white epoxy coated wire	2 white epoxy coated wire
	Handle	ABS Plastic, recessed		
	Solid Door	1 Stainless Steel Door	2 Stainless Steel Doors	2 Stainless Steel Doors
	Door Gasket	Tongue and groove, easy to clean & replace		
	Hinges	Stainless steel	Stainless steel	Stainless steel
	Pilasters and Shelf Clips	Stainless steel	Stainless steel	Stainless steel
	Floor	Rounded, coved corners		
	Casters	(2) Locking, (2) non-locking		
Temperature Range	-8°F to 0°F	-8°F to 0°F	-8°F to 0°F	
Refrigeration System	Forced Air	Forced Air	Forced Air	

	Refrigerant	R290	R291	R292
	Expansion Device	Capillary Tube	Capillary Tube	Capillary Tube
	Defrost method	Automatic	Automatic	Automatic
	Compressor Type	Hermetic compressor		
	Condenser Type	Air cooled, electrostatic coated copper tube		
	Evaporator Type	Air cooled, electrostatic coated copper tube		
	Humidity control	Hot gas condensation evaporation		
	Power	115/60/1	115/60/1	115/60/1
	Plug	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P	8 Ft NEMA 5-15P
	Horse Power	1/6	1/5	1/5
	Kilowatts per 24 Hours			
	Amperage	2.8	2.8	2.8
	Shipping Dimensions			
	Shipping Weight			
	Palletized	Yes, wood, front/back loading		
	Material	Wood, card board, styrofoam, plastic wrap		
	UPC GTIN			
	Digital Temperature Microprocessor	Precision temperature pre-set to 33°F to 41°F. Adjustable set-point, temperature differential, evaporator fan on/off cycles & air defrost cycles.		
	Key Pad	Adjustable, tactile key pad		
	Screen	2" blue LCD	2" blue LCD	2" blue LCD
	Water resistant	Yes	Yes	Yes
Warranty	Compressor	5 Years	5 Years	5 Years
	Parts	2 Years	2 Years	2 Years
	Labor	2 Year	2 Year	2 Year
	ETL sanitation (conforms to NSF 7 Foodservice), ETL electrical (US and Canada)			
Application	For Commercial Kitchens (not for residential use)			
Company Motto	Best Build, Period.			

